

A noncorrosive, non-ammoniated, solvent based stripper for the removal of metal cross-linked floor finishes from a variety of floors.

Where To Use


Asphalt Tile	Rubber Tile	Vinyl Tile
Linoleum	Terrazzo	Concrete
Other floor surfaces except wood.		

Dilutions:

Light Stripping: Dilute 1 part product with 8 parts water.
Regular Stripping: Dilute 1 part product with 4 parts water.
Heavy Duty Stripping: Dilute 1 part product with 2 parts water.

Diluciones:

Raspado Ligero: Diluya 1 parte de producto con 8 partes de agua.
Raspado Regular: Diluya 1 parte de producto con 4 partes de agua.
Raspado para Tareas Pesadas: Diluya 1 parte de producto con 2 partes de agua.



DIRECTIONS: Dust mop and scrape gum, etc. from floor. Dilute product into a mop bucket according to the directions above. Apply solution generously to a workable area. Allow solution to sit for 5 to 10 minutes. Floor must remain wet. Agitate solution with a floor machine using an aggressive stripping pad (black or brown). If needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Remove the old finish and stripping solution with a mop or wet vac. Inspect entire floor to assure stripping has been complete. Reapply to areas that require additional stripping and pick up solution. Allow floor to dry completely prior to applying sealer or finish. Rinsing is not necessary but ensures a good, clean, residue free floor.

INDICACIONES: Trapee y quite goma de mascar, etc., del piso. Diluya el producto en una cubeta de acuerdo a las indicaciones de arriba. Aplique la solución abundantemente a un área trabajable. Permita que la solución repose por 5 a 10 minutos. El piso debe permanecer mojado. Agite la solución con una máquina para pisos usando una paleta raspadora agresiva (negra o café). Si es necesario, raspe las terminaciones y esquinas manualmente con la esquina de una almohadilla o el centro de la almohadilla raspadora. Remueva el acabado antiguo y solución raspadora con un trapeador o aspiradora de vacío. Revise el piso entero para asegurarse de que un raspado completo ha sido realizado. Vuelva a aplicar en áreas que requieren raspado adicional y recoga la solución. Permita que el piso se seque completamente antes de aplicar un sellador o acabado. Enjuagado no es necesario pero asegura un piso limpio y libre de residuos.

FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. CAUTION! This product has a strong alkaline action and may cause eye burns and skin irritation. For personal protection use safety glasses and rubber gloves. Use with adequate ventilation. Wash after handling. Do not allow this product to come in contact with acids. Undiluted product may damage or discolor surfaces. Do not allow to dry on glass or painted surfaces. Do not move to unmarked containers. Spilled material is slippery. Please rinse empty containers and offer for recycling. Dispose of any excess or unused product and any waste materials according to local, state or federal requirements.

PARA USO INDUSTRIAL SOLAMENTE. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. ¡PRECAUCIÓN! Este producto tiene una acción fuertemente alcalina y puede causar quemaduras en los ojos y la irritación de la piel. Para protección personal use lentes de seguridad y guantes de goma. Usar con ventilación adecuada. Lave después de manipular. No permita que este producto entre en contacto con ácidos. El producto no diluido puede dañar o desteñir superficies. No le permita secarse en vidrios o superficies pintadas. No transfiera a envases sin marcas. Derrames de material son resbaladizos. Por favor enjuague envases vacíos y recíclelos. Elimine cualquier exceso de producto, o producto no utilizado y cualquier material de desecho de acuerdo a los requerimientos locales, estatales o federales.

Technical Specifications

COLOR:..... Colorless	VISCOSITY:..... Water Thin
FORM:..... Liquid	STORAGE(Unopened):... 1 Year @R.T.
SCENT:..... Slight solvent	BIODEGRADABLE: Yes
pH: 12.0 +/- 0.5	WEIGHT/GAL:8.3
FLASH POINT:.. None	SHIPPING CLASS:.....None
FOAM:..... Low	PACKAGING:5 gal box
TYPE: Noncorrosive Stripper	

