

A highly responsive metal cross-linked protective floor finish. Formulated for easy maintenance and high gloss. Can be maintained with scrub and re-coat procedures, spray buffing or burnishing.



Where To Use

Asphalt Tile	Rubber Tile	Vinyl Tile
Linoleum	Terrazzo	Concrete
Other floor surfaces except wood.		

Dilution: This product is ready-to-use.

Dilucion: Este producto está listo para usar.

Directions: Prior to application, the floor should be completely stripped of all old finish, scrubbed or cleaned. The floor should be completely dry before applying the first coat and all subsequent coats. Pour undiluted product into a clean dry mop bucket with ringer. Apply in thin coats, evenly. On unsealed floors, apply 4 or 5 coats. On cleaned or scrubbed floors, apply as needed. Be sure to use a different mop for stripping and for applying finish. Allow 24 hours for curing before burnishing.

Indicaciones: Antes de su aplicación, el piso debe ser raspado totalmente de todo acabado antiguo, restregado o limpiado. El piso debe estar totalmente seco antes de aplicar la primera capa y todas las capas siguientes. Vierta el producto sin diluir en un trapeador limpio y seco cubo con timbre. Aplíquese uniformemente en capas delgadas. En pisos sin sellar, aplique 4 o 5 capas. En pisos limpios o fregados, aplíquese según se necesite. Asegúrese de utilizar un trapeador diferente para separar y para aplicar el acabado. Permita 24 horas para el curado antes de pulir.

FOR INDUSTRIAL USE ONLY. KEEP OUT OF REACH OF CHILDREN. CAUTION! This product may cause irritation of the eyes and skin. For personal protection use safety glasses and rubber gloves. Use with adequate ventilation. Wash after handling. This product may damage or discolor surfaces other than those for which its use is intended. Do not allow to dry on glass or painted surfaces. Do not move to unmarked containers. Spilled material is slippery. Please rinse empty containers and offer for recycling. Dispose of any excess or unused product and any waste materials according to local, state or federal requirements.

PARA USO INDUSTRIAL SOLAMENTE. MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. ¡PRECAUCIÓN! Este producto puede causar irritación a los ojos y piel. Para protección personal use lentes de seguridad y guantes de goma. Usar con ventilación adecuada. Lave después de manipular. Este producto puede dañar o decolorar las superficies que no sean adecuadas para su uso. No le permita secarse en vidrios o superficies pintadas. No transfiera a envases sin marcas. Derrames de material son resbaladizos. Por favor enjuague envases vacíos y recíclelos. Elimine cualquier exceso de producto, o producto no utilizado y cualquier material de desecho de acuerdo a los requerimientos locales, estatales o federales.

Technical Specifications

COLOR: Milk-white	TYPE: Acrylic Polymer Finish
FORM: Liquid	SOLID CONTENT: 23% (+/-1%)
SCENT: Mild Solvent/Polymer	INITIAL GLOSS: High
pH: 8.4 +/- 0.5	RECOAT DRYING TIME: 30 Minutes
FLASH POINT: None	COVERAGE: 2500 - 3000 sq ft.
FOAM: Low	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: 0.5 or higher
STORAGE(Unopened):.....1 Year @R.T.	REMOVABILITY: Excellent
WEIGHT/GAL: 8.5	SCUFF RESISTANCE..... Very Good
SHIPPING CLASS: None	DETERGENT RESISTANT Very Good
PACKAGING: 4x1, 5 gal

