

A urethane fortified, penetrating floor sealer formulated for porous surfaces such as terrazzo, quarry tile, ceramic and other stone floors. This product is also the perfect product for sealing both old and new linoleum flooring. Ura Seal addresses the bonding concern which is present with both stone and linoleum flooring.



Where To Use

For all types of stone floor finishes.

Vinyl Tile	Vinyl Asbestos	Sealed Wood
Asphalt Tile	Linoleum	

Dilution

As is.

Directions

Prior to application, floor should be completely stripped of all old sealers and finishes. The surface should be completely clean and dry. Apply two coats of Ura Seal, allowing adequate drying time between coats. To obtain a higher depth of gloss appearance. Follow with additional coats of Ura Seal or Terra Brite on stone floors. For linoleum follow with any of the other Simoniz® floor finishes such as Wet Look Plus or Premier Plus. Be sure to use a different mop for sealers and finishes. When applying to stone surfaces, use a brush, roller or applicator. When applying to linoleum or any other tile flooring, use a finish mop.

Technical Specifications

COLOR: Transparent	TYPE: Urethane Fortified Sealer
FORM: Liquid	SOLID CONTENT: 18%
SCENT: Odorless	INITIAL GLOSS: Good
pH: 8.0	RECOAT DRYING TIME: < 30 Minutes
FLASH POINT: None	COVERAGE: 2500 – 3000 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: Min. 0.5
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Good
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Very Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: . Excellent
SHIPPING CLASS: None	HIGH SPEED BURNISH: No
PACKAGING: 4x1, 5 gal, 55 gal	

