



WORK HORSE

Acrylic Floor Finish

DESCRIPTION

All acrylic copolymers metal cross-linked to resist the scuffing of floors. It is user friendly, fast laying, quick drying, and its initial gloss is excellent for use in schools, hospitals, or other high traffic areas where high or low speed buffing without powdering is desired. Synthetic detergents and emulsifiers have little effect on this product's gloss and durability. Surfaces coated with this finish will shine even after repeated abuse. Damp mopping and cleaning as well as the removal of greasy soils are a breeze when done over Work Horse coatings. A wide range of flexibility allows this product to be used on any surface not harmed by water.

This floor finish contains cross metal linked copolymers in an opaque emulsion. It is low foaming and will retain a wet look. It dries clear, without streaking or cracking and is highly resistant to detergents and scratches.

INSTRUCTIONS

For best results apply full strength over freshly stripped and rinsed floor. Apply first coat lightly, being more concerned with even coverage than quantity of finish applied. Allow approximately 15 to 20 minutes drying time between coats then apply a second coat a little heavier than the first. Repeat this procedure for up to 4 coats if necessary or desired. Please allow 24 hours cure time after last coat before high speed burnishing; although under some conditions burnishing between coats can be performed if proper care is taken.

FEATURES

- User Friendly
- Low or high speed buffing
- Non-corrosive, nontoxic
- Resists scuffing and harsh detergents

SPECIFICATIONS

Appearance:	White Emulsion	pH:	8.9
Odor:	Solvent	Biodegradable:	Yes
Specific gravity:	8.5	Durability:	Excellent