

An economical, metal cross-linked floor finish/sealer for use on resilient floors.



Where To Use

On low traffic areas, low maintenance programs

Vinyl Tile	Linoleum	Sealed Wood
Stone	Rubber	Asbestos Tile
Concrete	Asphalt Tile	Terrazzo

Dilution

As is.

Directions

Prior to application, floor should be completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Manual. The floor should be completely dry before applying first coat and all subsequent coats. Apply thin coats, evenly. If the floor is old or in poor condition, two coats of Super Sealer are recommended. On unsealed floors, apply 4-5 coats. On cleaned or scrubbed floors, apply as needed. Be sure to use a different mop for stripping, sealing and finish. Dust and damp mop on a regular basis. Spray buff periodically to maintain and enhance the shine.

Technical Specifications

COLOR: Milk-white	TYPE: Acrylic Polymer Sealer/Finish
FORM: Liquid	SOLID CONTENT: 16%
SCENT: Mild Solvent/Polymer	INITIAL GLOSS: Excellent
pH: 8.0	RECOAT DRYING TIME: 30 Minutes
FLASH POINT: None	COVERAGE: 2500 sq. ft.
FOAM: None	LEVELING: Good
VISCOSITY: Water Thin	SLIP COEFFICIENT:05
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Excellent
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: ... Good
SHIPPING CLASS: None	HIGH SPEED BURNISH: No
PACKAGING: 4x1, 5 gal, 55 gal	

