

A superior quality sealer/finish formulated to seal and protect terrazzo floors, quarry tile and other stone flooring. Offers excellent gloss and durability and can be maintained at any speed for long lasting shine.



Where To Use

Terrazzo Concrete
Quarry Tile Ceramic Tile

Dilution

As is.

Directions

To seal and protect floors, use a minimum of three coats. For optimum gloss, seal with two coats of Simoniz® Ura Seal. Prior to applying finish, make sure that the floor has been completely stripped of all old finish. This can be accomplished by using a Simoniz® stripper. Follow stripping procedure from the Simoniz® Floor Care Manual. Apply this product to a dry floor that has been stripped, scrubbed or cleaned. Apply evenly in thin coats. On cleaned and scrubbed floors apply as necessary. Be sure to use a different mop for stripping, sealing and finishing. Allow 24 hours for curing before burnishing. Floors should be dusted and damp mopped on a regular basis to keep a long lasting shine.

Technical Specifications

COLOR: Milk-white	TYPE: Acrylic Polymer Sealer/Finish
FORM: Liquid	SOLID CONTENT: 20%
SCENT: Mild Solvent/Polymer	INITIAL GLOSS: High
pH: 8.0	RECOAT DRYING TIME: 30 Minutes
FLASH POINT: None	COVERAGE: 2500 - 3000 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: 0.55
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Excellent
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Very Good
WEIGHT/GAL: 8.5 lbs.	DETERGENT RESISTANT: . Very Good
SHIPPING CLASS: None	HIGH SPEED BURNISH: Yes
PACKAGING: 4x1, 5 gal, 55 gal	

