

A urethane fortified, penetrating floor sealer formulated for porous surfaces such as terrazzo, quarry tile, ceramic and other stone floors. Addresses the bonding concern which is present with stone flooring.



Where To Use

For all types of stone floor finishes.
Terrazzo Ceramic Tile
Quarry Tile Brick
Concrete

Dilution

As is.

Directions

The surface should be in good condition and completely clean and dry. Apply with brush, roller or applicator. Apply two coats, allowing adequate drying time between coats. To obtain a high gloss appearance follow with additional coats of Ultra Line Vista Floor Finish. Be sure to use a different mop for sealers and finishes.

Technical Specifications

COLOR: Transparent	TYPE: Urethane Fortified Sealer
FORM: Liquid	SOLID CONTENT: 20%
SCENT: Odorless	INITIAL GLOSS: Good
pH: 8.0	RECOAT DRYING TIME: < 30 Minutes
FLASH POINT: None	COVERAGE: 2500 – 3000 sq. ft.
FOAM: None	LEVELING: Excellent
VISCOSITY: Water Thin	SLIP COEFFICIENT: Min. 0.5
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Good
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Very Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: . Excellent
SHIPPING CLASS: None	HIGH SPEED BURNISH: No
PACKAGING: 4x1, 5 gal	

