

Dustmop Treatment

S3343

Improves dust pick-up on mops and cloths by converting dust into heavy lint particles that shake off easily into a dustpan. Keeps dust from becoming airborne and spreading. Reduces contamination of other surfaces. Leaves no oily residue and extends the life of the floor finish.



Where To Use

Spray on dust mop or cloth to control dust from scattering while you are cleaning:

Floors	Concrete	Vinyl Tile	Linoleum Floors
Wood	Formica	Auto Interiors	Window Frames
Plastics	Furniture	Venetian Blinds	Composition Floors

Directions

Please adhere to the following directions carefully.

On new or freshly laundered mops, 2 or 3 applications may be necessary for complete penetration.

Mop Preparation - Hold can upright 6 to 8 inches from mop head. Spray mop surface for 10 to 15 seconds for use on unsealed wood or concrete floors. Spray 5 to 10 seconds for sealed wood or finished asphalt tile, rubber tile, vinyl tile or composition floors.

Dust Cloths - Hold can upright 6 to 8 inches from cloth. Spray cloth surface for 5 to 10 seconds.

Technical Specifications

CAN SIZE: ...20 oz.	NET WEIGHT:17 oz.
SCENT:Pleasant	USDA RATING:N/A
TYPE:Aerosol	PROPELLANT:Hydrocarbon
pH:N/A	SPRAY PATTERN: .Misty Solid Cone
COLOR:Clear	FLAMMABILITY:Flammable - per CPSC Flame Ext. Test in 16 CFR 1500.45.



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070

www.simoniz.com www.simonizjanitorial.com

All labels are GHS compliant.