

GRIP COAT CONTRACTOR

G0005005B

A premium floor sealer/finish with high gloss levels. Designed specifically to achieve outstanding performance when used with high speed equipment. Easy to apply and extremely durable. Formulated for easy maintenance and high gloss.



Where To Use

All resilient floors, highly visible areas, supermarkets and medium maintenance programs.

Terrazzo	Vinyl Tile	Rubber Tile
Concrete	Asbestos Tile	Linoleum
Stone	Sealed Wood	VCT

Dilution

As is.

Directions

Ensure that the floor has been completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Training on our website. The floor should be completely dry before applying the first coat and all subsequent coats. Apply in thin coats, evenly. If the floor is old or in poor condition, two coats of Simoniz® Grip Seal or Super Sealer are recommended prior to finish. On unsealed floors, apply 5 - 6 coats. On cleaned or scrubbed floors apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing. For superior results, use with regular weekly UHS burnishing.

Technical Specifications

COLOR:Milk-white	FORM:Liquid
SOLID CONTENT:High	SCENT:Mild Solvent/Polymer
INITIAL GLOSS:High	pH:8.0
RECOAT DRYING TIME:<30 Minutes	FLASH POINT:None
COVERAGE:2500 - 3000 sq. ft.	FOAM:None
LEVELING:Excellent	VISCOSITY:Water Thin
SLIP COEFFICIENT:0.53	STORAGE(Unopened):1 Year @R.T.
REMOVABILITY:Excellent	BIODEGRADABLE:Yes
SCUFF RESISTANCE:Very Good	WEIGHT/GAL:8.5
DETERGENT RESISTANT: ..Very Good	SHIPPING CLASS:None
HIGH SPEED BURNISH:Yes	PACKAGING:4x1, 5 gal, 55 gal
TYPE:Acrylic Polymer Sealer/Finish	



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 i 860-646-0172 i FAX 860-645-6070

www.simoniz.com www.simonizjanitorial.com

All labels are GHS compliant.