

Grip Seal is a true underlayment or stand-alone sealer which has excellent performance in both circumstances. Grip Seal is Urethane fortified and considered a semi-permanent sealer. Because of its durability Grip Seal will withstand several conventional strip cycles.



Where To Use

Concrete - Polished concrete - Stone
Most other hard surfaces that Floor Finish is typically applied
Retail Stores
Warehouses
Garage Floors

Dilution

As is

Directions

1. Strip Floor removing all previous Floor Finish
2. Remove Stripping Solution by rinsing several times with water. Using a wet vac can speed the pickup process
3. After the floor has dried completely, apply 1 to 2 coats of Grip Seal using Finish Mop or Flat Mop Applicator
4. Allow 30-45 minutes drying time
5. Reapply Grip Seal and allow to fully dry
6. For additional gloss enhancement, follow with 1-2 coats of Grip Coat Finish

Technical Specifications

COLOR: White Opaque	VISCOSITY: Water Thin
FORM: Liquid	STORAGE(Unopened):1 Year @R.T.
SCENT: Mild solvent/polymer	BIODEGRADABLE: Yes
pH: 8.0-9.0	WEIGHT/GAL:8.45 lbs/gal
FLASH POINT: .. None	SHIPPING CLASS:None
FOAM: Low	PACKAGING:.....5 gallon bag in box
TYPE: Urethane Sealer	SLIP COEFFICIENT:0.7

