Honorable Discharge

H1523

A concentrated, "oil splitting" formulation for pressure cleaning in a water reclaimation environment. It contains a unique detergent system that allows oils to rapidly "split off" from the cleaning solution.



Where To Use

Garages Dump Trucks Fleet Cleaning Pressure Washing

Construction Equipment Water Reclaim Systems

Dilution

General - 1/40 (3 oz./gallon) Heavy-duty - 1/20 (6 oz./gallon)

Directions

For pressure cleaning, set machine to dilute according to dilution table above. Apply solution to a workable area being sure to concentrate the product on the heavy soiled area. Let solution dwell to allow the grease cutting ingredients to loosen soil. Agitate with a soft bristle truck brush if necessary. High pressure rinse with hot water. Detergents used with reclaim systems should be diluted with fresh water whenever possible. This will ensure that the solution will work optimally.

Technical Specifications

| COLOR: Transparent | VISCOSITY:Water thin |
|-----------------------------------------------|--------------------------------|
| FORM: Liquid | STORAGE(Unopened):1 Year @R.T. |
| SCENT: Odorless | BIODEGRADABLE: Yes |
| pH:13.2 | WEIGHT/GAL: 8.7 lbs. |
| FLASH POINT None | SHIPPING CLASS:None |
| FOAM:Low | PACKAGING:5 gal, 55 gal |
| TYPE: Oil Splitting Pressure Washer Detergent | |



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070

www.simonizusa.com