

A heavy-duty, non-caustic alkaline detergent. Contains special inhibitors to stop rusting, removes carbon, heavy grease and oily soils. Ideal for cleaning aluminum motor blocks, heads, castings, crank shafts and similar objects. Does not contain chromium salts or chlorinated solvent. Contains naturally occurring d-limonene solvent for added cleaning and degreasing.



Where To Use

- Spray Cabinets
- Stationary Parts Washers
- Hot Tank Cleaning Operations

Dilution & Directions

Dilution should be in the range of 2-8 ounces of detergent per gallon capacity depending on soil load. Temperature range (140°-180° F). Typical starting solutions in 160° F at ounces per gallon. Add powder slowly to avoid caking. Cold water can cause foam to appear.

Technical Specifications

COLOR:	Yellow	VISCOSITY:	N/A
FORM:	Powder	STORAGE(Unopened):..	1 Year @R.T.
SCENT:	Citrus	BIODEGRADABLE: ...	Yes
pH:	N/A	WEIGHT /GAL:	N/A
FLASH POINT:	None	SHIPPING CLASS:	8, Hydrate Mixture Packing Gr III
FOAM:	None	PACKAGING:	50 lb, 100 lb, 420 lb
TYPE:	Non-caustic, d-Limonene Parts Washer Powder		

