

An acrylic floor sealer with superior bonding and leveling qualities. This high quality undercoating increases depth of gloss and provides for a longer wearing finish.



Where To Use

For all types of floor finishes.

Vinyl Tile Vinyl Asbestos Sealed Wood
Asphalt Tile Linoleum

Dilution

As is.

Directions

Prior to application, floor should be completely stripped of all old finishes. Follow stripping procedures from the Simoniz® Floor Care Manual. Apply two coats of Super Sealer, allowing adequate drying time between coats. After second coat has dried completely, start the finish process. Be sure to use a different mop for sealing and finishing.

Technical Specifications

COLOR: Hazy-white	TYPE: Acrylic Polymer Sealer
FORM: Liquid	SOLID CONTENT: 18%
SCENT: Odorless	INITIAL GLOSS: Good
pH: 8.0	RECOAT DRYING TIME: 30 Minutes
FLASH POINT: None	COVERAGE: 2500 sq. ft.
FOAM: None	LEVELING: Good
VISCOSITY: Water Thin	SLIP COEFFICIENT: 0.5
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: Good
BIODEGRADABLE: Yes	SCUFF RESISTANCE: Good
WEIGHT/GAL: 8.5	DETERGENT RESISTANT: . Excellent
SHIPPING CLASS: None	HIGH SPEED BURNISH: No
PACKAGING: 4x1, 5 gal, 55 gal	

