

*Heavy duty no scrub floor finish stripper. Quickly liquefies finish for easy removal.*



### Where To Use

Large strip jobs with heavy build up of old finishes or urethane fortified finishes.

Vinyl Tile	Vinyl Asbestos	Asphalt Tile
Concrete	Rubber	

### Dilution

Heavy stripping – 1/4 (32 oz./gallon)

Medium – 1/8 (16 oz./gallon)

Light – 1/20 (6.5 oz./gallon)

### Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to cool or room temperature water. If cold water must be used, allow additional dwell time. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet. The only agitation necessary will be from mopping action when applying the stripper. For heavy build up, agitate solution with a floor machine using an aggressive stripping pad (black or brown) if needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vac or mop and bucket. Inspect the entire floor to ensure that complete stripping has been accomplished. Reapply where necessary. Rinse thoroughly with cool, clear water. Allow floor to dry completely prior to applying sealer or finish.

### Technical Specifications

COLOR: ..... Transparent	VISCOSITY: ..... Water Thin
FORM: ..... Liquid	STORAGE(Unopened):...1 Year @R.T.
SCENT: ..... Slight solvent	BIODEGRADABLE: ...Yes
pH: ..... 13.6	WEIGHT/GAL: .....8.4
FLASH POINT: None	SHIPPING CLASS: .....8, packing Gr III
FOAM: ..... Low	PACKAGING: .....4x1, 5 gal
TYPE: ..... Heavy Duty No Scrub Caustic Stripper	

