

A high quality/high solid product that maintains the "wet look - no skid" finish on floors. Used routinely for low speed floor maintenance between strippings. Can be used less frequently than other common spray buff products.



Where To Use

On all traffic areas, all maintenance programs.

Vinyl Tile	Linoleum	Sealed Wood
Stone	Rubber	Asbestos Tile
Concrete	Asphalt Tile	Terrazzo

Dilution

As is.

Directions

Sweep dirt from floor and remove obvious soil buildup. Wash with neutral detergent such as ULTRA LINE NEUTRAL CLEANER and let dry completely. Spray in 3 to 4 foot wide sections in front of machine and buff to a high shine paying close attention to heavy scuff marks.. One gallon covers approximately 2000 square feet.

Technical Specifications

COLOR:	Milk-white	TYPE:	Acrylic Polymer Spray Buff
FORM:	Liquid	SOLID CONTENT:	6%
SCENT:	Odorless	INITIAL GLOSS:	Excellent
pH:	8.0	RECOAT DRYING TIME:	N/A
FLASH POINT:	None	COVERAGE:	2000 - 2500 sq ft
FOAM:	None	LEVELING:	Excellent
VISCOSITY:	Water Thin	SLIP COEFFICIENT:	0.5
STORAGE(Unopened):	. 1 Year @R.T.	REMOVABILITY:	Excellent
BIODEGRADABLE:	Yes	SCUFF RESISTANCE:	Excellent
WEIGHT/GAL:	8.4 lbs.	DETERGENT RESISTANT:	Excellent
SHIPPING CLASS:	None	HIGH SPEED BURNISH:	No
PACKAGING:	12x32, 4x1		

