

Ultra Line 33-High Solids

UL0700

33% solid content floor sealer/finish - requires half the coats then conventional floor finishes. Durable, high gloss, labor saving floor finish.



Where To Use

All resilient floors, highly visible areas, supermarkets, office building, schools

| | | |
|----------|---------------|-------------|
| Terrazzo | Vinyl Tile | Rubber Tile |
| Concrete | Asbestos Tile | Linoleum |
| Stone | Sealed Wood | |

Dilution

As is.

Directions

Ensure that the floor has been completely stripped off all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Manual. The floor should be completely dry before applying the first coat and all subsequent coats. Apply thin coats, evenly. On unsealed floors, apply 2-3 coats. On cleaned or scrubbed floors apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing. For superior results, use with regular maintenance.

Technical Specifications

| | | | |
|-----------------------|----------------------|---------------------------|------------------------|
| COLOR: | Milk-white | TYPE: | Acrylic Polymer Finish |
| FORM: | Liquid | SOLID CONTENT: | 33% |
| SCENT: | Mild Solvent/Polymer | INITIAL GLOSS: | High |
| pH: | 8.0 | RECOAT DRYING TIME: | 30 Minutes Minimum |
| FLASH POINT: | None | COVERAGE: | 2500 - 3000 sq ft |
| FOAM: | None | LEVELING: | Excellent |
| VISCOSITY: | Water Thin | SLIP COEFFICIENT: | 0.52 |
| STORAGE(Unopened): . | 1 Year @R.T. | REMOVABILITY: | Excellent |
| BIODEGRADABLE: | Yes | SCUFF RESISTANCE: | Excellent |
| WEIGHT/GAL: | 8.4 lbs. | DETERGENT RESISTANT: . | Excellent |
| SHIPPING CLASS: | None | HIGH SPEED BURNISH: | Yes |
| PACKAGING: | 4x1, 5 gal, 55 gal | | |



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070

www.simoniz.com

www.simonizjanitorial.com