Ultra Line Stripper

Heavy duty no scrub floor finish stripper. Quickly liquefies finish for easy removal. High dilution, super aggressive for the toughest strip outs.



Where To Use

Large strip jobs with heavy build up of old finishes or urethane fortified finishes. Vinyl Tile Vinyl Asbestos Asphalt Tile Concrete Rubber

Dilution

Heavy stripping – 1/8 (16 oz./gallon) Medium – 1/16 (8 oz./gallon) Light – 1/32 (4 oz./gallon)

Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to cool or room temperature water. If cold water must be used, allow additional dwell time. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet if not using a stripping machine. The only agitation necessary will be from mopping action when applying the stripper. For heavy build up, agitate solution with a floor machine using an aggressive stripping pad (black or brown) if needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vac or mop and bucket. Inspect the entire floor to ensure that complete stripping has been accomplished. Reapply where necessary. Rinse thoroughly with cool, clear water. Allow floor to dry completely prior to applying sealer or finish.

Technical Specifications

COLOR:Transparent Purple VISCOSITY:Water Thin	
FORM:Liquid	STORAGE(Unopened):1 Year @R.T.
SCENT:Slight solvent	BIODEGRADABLE:Yes
рН:13.6	WEIGHT/GAL:8.4
FLASH POINT: .None	SHIPPING CLASS:8, packing Gr III
FOAM:Low	PACKAGING:4x1, 5 gal, 55 gal
TYPE:Heavy Duty No Scrub Floor Finish Stripper	



Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070 www.simonizjanitorial.com

www.simoniz.com