

A non-ammoniated, no-rinse, solvent-based stripper for the removal of metal cross-linked floor finishes from all types of floors.



Where To Use

Vinyl Tile Asbestos Tile
Concrete Terrazzo
Stone Asphalt Tile

Dilution

Heavy stripping - _ (32 ounces per gallon)
Medium - 1/8 (16 ounces per gallon)
Light - 1/16 (8 ounces per gallon)

Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from the above table and add the appropriate amount of product to cool or room temperature water. Apply solution generously to a workable area. Allow solution to sit for 5 to 10 minutes. Floor must remain wet. Agitate solution with a floor machine using an aggressive stripping pad (black or brown). If needed, hand scrub edges and corners with an edge pad or center of the scrubbing pad. Remove the old finish and stripping solution with a mop or wet vac. Inspect entire floor to assure stripping has been complete. Reapply to areas that require additional stripping and pick up solution. Allow floor to dry completely prior to applying sealer or finish. Rinsing is not necessary but ensures a good, clean, residue free floor.

Si no puede leer Inglés, no trate de utilizar este producto hasta que esté plenamente instrucciones sobre su manejo adecuado y seguro.

Technical Specifications

COLOR: Transparent	VISCOSITY:Water Thin
FORM: Liquid	STORAGE(Unopened):..1 Year @R.T.
SCENT: Solvent	BIODEGRADABLE: ...Yes
pH: 13.2	WEIGHT/GAL:8.5
FLASH POINT: None	SHIPPING CLASS:6.1, packing or III
FOAM: None	PACKAGING:4x1, 5 gal, 55 gal
TYPE: No Rinse Stripper	

