

*A premium floor sealer/finish with high gloss levels. Designed specifically to achieve outstanding performance when used with high speed equipment. Easy to apply and extremely durable. Formulated for easy maintenance and high gloss.*



### Where To Use

All resilient floors, highly visible areas, supermarkets and medium maintenance programs.

Terrazzo	Vinyl Tile	Rubber Tile
Concrete	Asbestos Tile	Linoleum
Stone	Sealed Wood	

### Dilution

As is.

### Directions

Ensure that the floor has been completely stripped of all old finish, scrubbed or cleaned. Follow stripping procedure from the Simoniz® Floor Care Manual. The floor should be completely dry before applying the first coat and all subsequent coats. Apply in thin coats, evenly. If the floor is old or in poor condition, two coats of Simoniz® Super Sealer are recommended prior to finish. On unsealed floors, apply 5 - 6 coats. On cleaned or scrubbed floors apply as needed. Be sure to use a different mop for stripping, sealing and finish. Allow 24 hours for curing before burnishing. For superior results, use with regular weekly UHS burnishing.

## Technical Specifications

COLOR: ..... Milk-white	TYPE: ..... Acrylic Polymer Sealer/Finish
FORM: ..... Liquid	SOLID CONTENT: ..... 22%
SCENT: ..... Mild Solvent/Polymer	INITIAL GLOSS: ..... High
pH: ..... 8.0	RECOAT DRYING TIME: .... <30 Minutes
FLASH POINT: ..... None	COVERAGE: ..... 2500 - 3000 sq. ft.
FOAM: ..... None	LEVELING: ..... Very Good
VISCOSITY: ..... Water Thin	SLIP COEFFICIENT: ..... 0.53
STORAGE(Unopened): . 1 Year @R.T.	REMOVABILITY: ..... Excellent
BIODEGRADABLE: ..... Yes	SCUFF RESISTANCE: ..... Good
WEIGHT/GAL: ..... 8.5	DETERGENT RESISTANT: . Very Good
SHIPPING CLASS: ..... None	HIGH SPEED BURNISH: ..... Yes
PACKAGING: ..... 4x1, 5 gal, 55 gal	

