



Dura-Brite 20

20% Premium Acrylic Floor Finish

Hard Floor Care

Description

A modern combination of acrylic copolymers metal cross linked to resist detergents and the scuffing of floors. It is fast laying, quick drying, and its initial gloss is excellent for use in schools, hospitals, or other high traffic areas where high or low speed buffing without powdering is desired. Dura-Brite 20 is perfect for low maintenance school systems or other areas where less maintenance is desired. Slip resistance meets or exceeds (ASTM D 2047-93) James Machine 0.5 minimum.

Directions for Use

For best results apply full strength over freshly stripped and rinsed floor. Apply first coat lightly, being more concerned with even coverage than quantity of finish applied. Allow approximately 30 to 40 minutes drying time, and then apply a second coat a little heavier than the first. Continue to apply additional coats until the desired gloss level and coverage is achieved. We recommend at least 5 coats for maximum gloss and protection. Dry times will vary based on the conditions, but will typically require 30 - 60 minutes between coats. Please allow 24 hours cure time after last coat before high speed burnishing with a pad any darker than beige. Under some conditions burnishing between coats can be performed if proper care is taken to test prior to doing.

Safety Cautions

- Keep out of reach of children
- Prior to using this or any cleaning product, make sure employees read and understand the hazard information found on the product label and Material Safety Data Sheet (MSDS). The label and MSDS will also provide information on handling precautions, protective equipment and first aid instructions which might be appropriate for this product.

Harvard Chemical Research, Inc
Atlanta, Georgia

Phone: 404-761-0657 Fax: 404-761-0709
www.hcronline.com

Features & Benefits

- Outstanding gloss off the mop
- Very durable, low maintenance finish
- Fast dry times
- Resist scuff marks and scratches
- Excellent recoatability
- Slip resistance meets or exceeds ASTM D2047 James Machine 0.5 minimum

Specifications

Appearance:	White Turbid Liquid
Odor:	Low
PH	8
Specific Gravity:	1.03
Biodegradable:	Yes
Solids:	20%

Dilution / Coverage

Coverage.....1500 - 2000 Sq. Ft / Gallon

Available Sizes

- Case/ 4x1 gallon: Item # 701304
- Pail/ 5 gallon: Item # 701305
- Drum/ 55 gallon: Item # 701306



Harvard Chemical
Research, Inc.