

Safety Data Sheet

1 – PRODUCT IDENTIFICATION

PRODUCT NAME: Gentle Touch
PRODUCT TYPE: Neutral liquid cleaning compound
PRODUCT NUMBER: G1325XXX (Last 3 characters vary with the packaging)
CONTROL NUMBER: G1325XXX

COMPANY: **Simoniz USA, Inc.**
201 Boston Turnpike
Bolton, CT 06043
1-800-227-5536
www.simoniz.com

EMERGENCY PHONE: (800) 255-3924 (CHEM-TEL)

2 – HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE:Eye Irritation (2)
SYMBOLS:



SIGNAL WORD: WARNING!
HAZARD STATEMENT: Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:

PREVENTION: Wash hands thoroughly after handling. Do not touch eyes. Wear protective gloves / protective clothing / eye protection / face protection.

RESPONSE: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical help.

STORAGE: N/A

DISPOSAL: N/A

3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT	C.A.S. NUMBER
Water	7732-18-5
Calcium Carbonate	1317-65-3
Smectite Clay	12199-37-0
Ethoxylated Coco Alkylbis(hydroxyethyl)methyl Ammonium Chlorides	61791-10-4

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals.

Safety Data Sheet

4 – FIRST-AID MEASURES

BREATHING (INHALATION):...Not likely to be inhaled in hazardous amounts. If signs of discomfort or irritation occur, remove to fresh air. If symptoms persist, seek medical attention.

SWALLOWING (INGESTION): .DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person. Get immediate medical attention!

EYES: Flush eyes with a large quantity of fresh water for at least 15 minutes. If irritation persists, seek medical attention.

SKIN (DERMAL): Not likely to irritate. Flush from skin and clothing with large amounts of fresh water. If irritation occurs, seek medical.

5 – FIRE-FIGHTING MEASURES

FLASHPOINT: This product is non-flammable.

EXTINGUISHING MEDIA: Use extinguishing media suitable for materials already burning.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters working in areas where this product is present should be equipped with an approved, fully enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS: None known.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES: Dike to prevent spillage into streams or sewer systems. Consult local, state and federal authorities.

WASTE DISPOSAL: As recommended by local, state and federal authorities.

7 – HANDLING and STORAGE

STORAGE: Store in a cool, well-ventilated area. Avoid overheating or freezing. Do NOT store this product in an unmarked container.

HANDLING: Wear eye protection if product is likely to make contact with eyes. Do NOT transfer this product to an unmarked container. Spilled material is slippery. Keep away from children!

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not usually needed. Vapors not normally harmful. If needed, use a NIOSH approved respirator.

PROTECTIVE CLOTHING: Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES: Under normal use according to label instructions, special protection should not be necessary. Wear eye protection if product is likely to make contact with eyes. Keep away from children!

Safety Data Sheet

INGREDIENT	C.A.S. NUMBER	OSHA PEL*
Water	7732-18-5	No limits established
Calcium Carbonate	1317-65-3	15 mg/m ³ (Total dust); 5 mg/m ³ (Respirable fraction)
Smectite Clay	12199-37-0	No limits established
Ethoxylated Coco Alkylbis(hydroxyethyl)methyl Ammonium Chlorides	61791-10-4	No limits established

*When OSHA 8-hour TWA; STEL; and Ceiling PEL values are not established, NIOSH REL and ACGIH TLV® values will be shown and indicated as such.

9 – PHYSICAL / CHEMICAL PROPERTIES

APPEARANCE & ODOR: Off-white to tan colored opaque liquid. Lemon scented.

ODOR THRESHOLD: N/A

pH: 6.5 – 9.0

MELTING POINT: N/A

FREEZING POINT: N/A

BOILING POINT: 210 degrees F.

BOILING POINT RANGE: N/A

FLASHPOINT: This product is non-flammable.

EVAPORATION RATE: N/A

FLAMMABILITY (solid/gas):..... N/A

EXPLOSION LIMITS:..... N/A

VAPOR PRESSURE:..... N/A

VAPOR DENSITY (AIR=1): Greater than 1.

SPECIFIC GRAVITY:..... 1.06

SOLUBILITY IN WATER: Dispersible.

PARTITION COEFFICIENT: N/A

AUTO-IGNITION TEMPERATURE:.....N/A

DECOMPOSITION TEMPERATURE:.....N/A

VISCOSITY:..... Significant Body

10 – STABILITY and REACTIVITY

STABILITY: Stable under normal conditions.

HAZARDOUS DECOMP.:..... This product not known to polymerize.

INCOMPATIBILITY:..... Do not mix with other chemicals.

11 – TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY:..... Absorption through eyes. Ingestion. Not likely to be absorbed through skin or inhaled in hazardous amounts.

LISTED CARCINOGEN:

IARC:

LISTED CARCINOGEN: Silica dust, crystalline, in the form of quartz or cristobalite.

C.A.S. NUMBER:..... 14808-60-7

GROUP/CLASSIFICATION: 1 / Carcinogenic to Humans.

Safety Data Sheet

OSHA:

LISTED CARCINOGEN: Respirable crystalline silica

C.A.S. NUMBER: 14808-60-7

GROUP/CLASSIFICATION: Potential Carcinogens

NTP:

LISTED CARCINOGEN: Quartz

C.A.S. NUMBER: 14808-60-7

GROUP/CLASSIFICATION: Known to be a human carcinogen.

MEDICAL CONDITION AGGRAVATED: None known.

INHALATION: Inhaling significant amounts of product may eventually cause irritation to the respiratory tract. Prolonged exposure to respirable crystalline silica can cause cancer and silicosis.

INGESTION: This product may cause irritation to esophagus and stomach if ingested.

EYES: This product can cause serious irritation and redness if not immediately flushed from eyes.

SKIN (DERMAL): Prolonged exposure to this product may eventually cause irritation or redness of the affected area of skin.

ACUTE TOXICITY* (ORAL): >5,000 mg/kg

ACUTE TOXICITY* (DERMAL): >5,000 mg/kg

ACUTE TOXICITY* (INHALATION): >20,000 ppm V (Gas), >20 mg/l (Vapor), >5 mg/l (Dust)

*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)

12 – ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION: N/A

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: As recommended by local, state and federal authorities.

14 – TRANSPORTATION INFORMATION


PROPER SHIPPING NAME: Not D.O.T. regulated.

HAZARD CLASS:

UN/NA NUMBER:

PACKAGING GROUP:

15 – REGULATIONS

California Proposition 65:  **WARNING:** This product can expose you to chemicals including 1,4-Dioxane, which are known to the State of California to cause cancer, and Ethylene Oxide, which are known to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Safety Data Sheet

INGREDIENT	C.A.S. NUMBER	Listed Date
1,4-Dioxane	123-91-1	01/01/1988 (Cancer)
Silica, crystalline (airborne particles of respirable size)	---	10/01/1988 (Cancer)
Ethylene Oxide	75-21-8	07/01/1987 (Cancer) 08/07/2009 (Developmental & Male Reproductive Toxicity) 02/27/1987 (Female Reproductive Toxicity)

Contents of this SDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

16 – OTHER INFORMATION

NFPA HEALTH:..... 2
NFPA FLAMMABILITY:..... 0
NFPA REACTIVITY:..... 0
NFPA OTHER:..... Alkali

ADDITIONAL: The information contained in this SDS is based on the data available to us from sources we believe to be reliable. No warranty or guaranty expressed or implied is made regarding the accuracy of this data or the results obtained from the reliance on this data. The manufacturer assumes no responsibility for injury from the use of this product. Be safe—read this product safety information and pass it on to all persons who may be exposed to this product. Federal law requires it. This product and/or all of its components are either included on or exempt from the TSCA Inventory of Chemical Substances.

REVISION DATE: 12/21/2023