## 1 - PRODUCT IDENTIFICATION

**PRODUCT NAME:** ...... Leather Cleaner & Conditioner **PRODUCT TYPE:** ..... Neutral Liquid Vehicle Dressing

CONTROL NUMBER:..... S3289XXX

COMPANY: ..... Simoniz USA, Inc.

201 Boston Turnpike Bolton, CT 06043 1-800-227-5536

www.simoniz.com

EMERGENCY PHONE:..... (800) 255-3924 (CHEM-TEL)

## 2 - HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE:..... Eye Irritation (2A)

SYMBOLS:.....



SIGNAL WORD:......WARNING!

**HAZARD STATEMENT:....** Causes serious eye irritation.

PRECAUTIONARY STATEMENTS:

**PREVENTION:** ...... Wash hands thoroughly after handling. Wear protective

gloves/protective clothing/eye protection/face protection.

**RESPONSE:**..... IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

STORAGE: ...... Store in a cool, well ventilated area. Avoid overheating or

freezing.

**DISPOSAL:** ...... As recommended by local, state and federal authorities.

## 3 - COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT
Water
7732-18-5
Hydrotreated Light Distillates
Polydimethylsiloxane
Tall Oil Diethanolamide
C.A.S. NUMBER
7732-18-5
64742-47-8
63148-62-9
68155-20-4

PAGE 1 of 5

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals

#### 4 - FIRST-AID MEASURES

**BREATHING (INHALATION):...** If victim shows signs of discomfort or irritation, remove to fresh air. If symptoms persist, get immediate medical attention.

**SWALLOWING (INGESTION)**:. DO NOT INDUCE VOMITING! Drink a large quantity of water or milk. Do not attempt to give liquids to an unconscious person.

Get immediate medical attention!

EYES: ...... Flush eyes with a large quantity of fresh water for at least 15

minutes. If irritation persists, consult a physician.

SKIN (DERMAL): ...... Flush from skin and clothing with large amounts of fresh water. If

irritation persists, consult physician. Wash contaminated clothing

before wearing.

## **5 – FIRE-FIGHTING MEASURES**

FLASHPOINT:.....>180 degrees F.

**EXTINGUISHING MEDIA:......** Water fog or fine spray. Carbon dioxide, Dry chemical or Alcohol

resistant foam.

**SPECIAL FIRE FIGHTING PROCEDURES:** .....Firefighters working in areas where this

product is present should be equipped with an approved, fully

enclosed SCBA.

UNUSUAL FIRE AND EXPLOSION HAZARDS:......None known.

## **6 – ACCIDENTAL RELEASE MEASURES**

SPILL PROCEDURES: ...... Dike to prevent spillage into streams or sewer systems. Consult

local, state and federal authorities.

**WASTE DISPOSAL:** ..... As recommended by local, state and federal authorities.

## 7 – HANDLING and STORAGE

STORAGE: ...... Store in a cool, well ventilated area. Avoid overheating or

freezing.

HANDLING:...... Do not place this product in an unmarked container! Keep away

from children! Spilled material is slippery. ATTENTION: Empty containers retain vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or

other sources of ignition. Do not reuse empty container.

## **8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**RESPIRATORY PROTECTION:**Not usually needed. Vapors not normally harmful. **PROTECTIVE CLOTHING:......** Nitrile or PVC gloves, and chemical splash goggles.

ADDITIONAL MEASURES: ..... Do not place this product in an unmarked container! Keep away

from children! Spilled material is slippery. ATTENTION: Empty containers retain vapor and product residue and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat, flame, sparks, static electricity or

other sources of ignition. Do not reuse empty container.

## INGREDIENT C.A.S. NUMBER PEL

| Water                          | 7732-18-5  | No limits established |
|--------------------------------|------------|-----------------------|
| Hydrotreated Light Distillates | 64742-47-8 | 500 ppm PEL           |
| Polydimethylsiloxane           | 63148-62-9 | No limits established |
| Tall Oil Diethanolamide        | 68155-20-4 | No limits established |

#### 9 - PHYSICAL / CHEMICAL PROPERITES

APPEARANCE & ODOR: ....... Slightly viscous white liquid, pleasantly scented.

MELTING POINT: ...... 210 degrees F.

FREEZING POINT: ..... N/A

BOILING POINT:......210 degrees F.

**BOILING POINT RANGE:.....** N/A

FLASHPOINT:.....>180 degrees F.

EVAPORATION RATE:...... N/A
FLAMMABILITY (solid/gas):.... N/A
EXPLOSION LIMITS:..... N/A
VAPOR PRESSURE: ...... N/A

VAPOR DENSITY (AIR=1):...... Greater than 1.

**SPECIFIC GRAVITY:.....** 0.99

**SOLUBILITY IN WATER: ......** Dispersible.

PARTITION COEFFICIENT: ..... N/A

**AUTO-IGNITION TEMPERATURE:**.....N/A **DECOMPOSITION TEMPERATURE:**.....N/A

VISCOSITY: ...... Significant body

## 10 - STABILITY and REACTIVITY

**STABILITY:** ...... Stable under normal conditions. **HAZARDOUS DECOMP.:** ...... This product not known to polymerize. **INCOMPATIBILITY:** ...... Do not mix with other chemicals.

# 11 - TOXICOLOGICAL INFORMATION ROUTE(S) OF ENTRY:.....Inhalation, skin absorption, or ingestion. **LISTED CARCINGGEN: ..........** This product contains a substance (Diethanolamine) known to produce cancer in laboratory animals. MEDICAL CONDITION AGGRAVATED:......May aggravate pre-existing dermatitis. INHALATION:...... Not likely to be inhaled in hazardous amounts. Avoid exposure to mists or vapors. Maintain adequate ventilation in the work area. INGESTION: ...... Swallowing even small amounts may be harmful. Effects may be nausea, headache, vomiting and central nervous system depression. **EYES:** ...... May cause severe eye irritation. Prolonged exposure may cause central nervous system depression. **ACUTE TOXICITY\* (ORAL):.....**>2000 mg/kg ACUTE TOXICITY\* (DERMAL):....>2000 mg/kg **ACUTE TOXCITY\* (INHALATION):.....**>20,000 ppm V (Gas), >20 mg/l (Vapor), >5 mg/I (Dust) \*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6) 12 - ECOLOGICAL INFORMATION **ENVIRONMENTAL FATE AND DISTRIBUTION: N/A**

## 13 - DISPOSAL CONSIDERATIONS

**WASTE DISPOSAL:** ...... As recommended by local, state and federal authorities.

## **14 – TRANSPORTATION INFORMATION**

PROPER SHIPPING NAME:..... Not D.O.T. regulated in these container sizes.

HAZARD CLASS:......

UN/NA NUMBER: ......

PACKAGING GROUP :......

## 15 - REGULATIONS

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

#### **16 – OTHER INFORMATION**

NFPA HEALTH: ...... 1
NFPA FLAMMABILITY: ..... 1
NFPA REACTIVITY: ..... 0
NFPA OTHER: ..... None

| ADDITIONAL: The information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in this SDS is based on the information contained in the informa |  |
|---|--|
| available to us from sources we believe to be reliab warranty or guaranty expressed or implied is made accuracy of this data or the results obtained from the this data. The manufacturer assumes no responsib from the use of this product. Be safe- read this product information and pass it on to all persons who may be this product. Federal law requires it. This product accomponents are either included on or exempt from Inventory of Chemical Substances.   | regarding the<br>ne reliance on<br>bility for injury<br>duct safety<br>be exposed to<br>nd/or all of its |