1 – PRODUCT IDENTIFICATION

PRODUCT NAME: Prism PRODUCT TYPE: Water Based Tire Dressing PRODUCT NUMBER: P3200XXX (Last 3 characters vary with the packaging) CONTROL NUMBER: P3200XXX

2 – HAZARDS IDENTIFICATION

CLASSIFICATION OF SUBSTANCE/MIXTURE: Skin Irritation (3) Eye Irritation (2/2A)

SYMBOLS:....



 SIGNAL WORD:
 WARNING!

 HAZARD STATEMENT:
 Causes mild skin irritation
 Causes serious eye irritation

 PRECAUTIONARY STATEMENTS:
 PREVENTION:
 Wash hands thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.

 RESPONSE:
 If skin irritation occurs: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. If eye irritation persists get medical advice/attention.

 STORAGE:
 N/A

3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENT Water

Polydimethylsiloxane Emulsion Odorless Mineral Spirits Acrylic Polymer Mixture

C.A.S. NUMBER 7732-18-5

Mixture 64741-65-7 Not Listed

PAGE 1 of 4

Percentages of ingredients are being withheld as trade secret information. This information will be disclosed as necessary to authorized individuals

4 – FIRST-AID MEASURES

BREATHING (INHALATION):	If victim shows signs of discomfort or irritation, remove to fresh air. If symptoms persist, get immediate medical attention.
SWALLOWING (INGESTION):	DO NOT INDUCE VOMITING! Drink a large quantity of water or
	milk. Do not attempt to give liquids to an unconscious person.
	Get immediate medical attention!
EYES:	Ingestion. Not likely to be inhaled in dangerous amounts.
SKIN (DERMAL):	Flush from skin and clothing with large amounts of fresh water. If irritation persists, consult physician. Wash contaminated clothing before wearing.

5 – FIRE-FIGHTING MEASURES

FLASHPOINT:	This product is non-flammable.
EXTINGUISHING MEDIA:	This product is non-flammable. Use extinguishing media suitable
	for materials already burning.
SPECIAL FIRE FIGHTING PRO	CEDURES:Firefighters working in areas where this
	product is present should be equipped with an approved, fully
	enclosed SCBA.
UNUSUAL FIRE AND EXPLOS	ION HAZARDS:None known.

6 – ACCIDENTAL RELEASE MEASURES

SPILL PROCEDURES:	Dike to prevent spillage into streams or sewer systems. Consult
	local, state and federal authorities.
WASTE DISPOSAL:	As recommended by local, state and federal authorities.

7 – HANDLING and STORAGE

STORAGE:	. Store in a cool, well ventilated area. Avoid overheating or
	freezing.
HANDLING:	. Do not place this product in an unmarked container. Avoid eye
	contact. Spilled material is slippery.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

RESPIRATORY PROTECTION: Not usually needed. Vapors not normally harmful. PROTECTIVE CLOTHING:...... Special protection not usually needed. Wear eye protection if product is likely to splash. ADDITIONAL MEASURES: Do not place this product in an unmarked container. Avoid eye contact. Spilled material is slippery.

INGREDIENT

C.A.S. NUMBER

PEL

Water Polydimethylsiloxane Emulsion Odorless Mineral Spirits Acrylic Polymer 7732-18-5 Mixture 64741-65-7 Not listed

No limits established No limits established 100 ppm TLV No limits established

9 – PHYSICAL / CHEMICAL PROPERITES

APPEARANCE & ODOR: Slightly viscous light blue liquid. Pleasantly scented. ODOR THRESHOLD: N/A **pH:**.....7.5-9.0 MELTING POINT: 210 degrees F. FREEZING POINT: N/A BOILING POINT:..... 210 degrees F. BOILING POINT RANGE: N/A FLASHPOINT: This product is non-flammable. EVAPORATION RATE: N/A FLAMMABILITY (solid/gas):.... N/A EXPLOSION LIMITS: N/A VAPOR PRESSURE:N/A VAPOR DENSITY (AIR=1):..... Greater than 1. SPECIFIC GRAVITY: 1.00 SOLUBILITY IN WATER: Completely soluble. PARTITION COEFFICIENT: N/A AUTO-IGNITION TEMPERATURE:.....N/A DECOMPOSITION TEMPERATURE:N/A VISCOSITY: Slight Body

10 – STABILITY and REACTIVITY

11 – TOXICOLOGICAL INFORMATION

ROUTE(S) OF ENTRY: Ingestion. Not likely to be inhaled in dangerous amounts. **LISTED CARCINOGEN:** None over 0.1%. **MEDICAL CONDITION AGGRAVATED:** May aggravate pre-existing dermatitis.

INHALATION:..... Not likely to be inhaled in hazardous amounts. Maintain adequate ventilation in the work area.

INGESTION: This material can cause irritation to the stomach and esophagus if ingested.

EYES: May cause eye irritation.

SKIN (DERMAL): Not likely to irritate. Prolonged exposure to undiluted product may cause irritation.

ACUTE TOXICITY* (ORAL):.....>2000 mg/kg ACUTE TOXICITY* (DERMAL):....>2000 mg/kg ACUTE TOXCITY* (INHALATION):....>20,000 ppm V (Gas), >20 mg/l (Vapor), >5 mg/l (Dust)

*Determined using the additivity formula for mixtures (GHS Purple Book, 3.1.3.6)

12 – ECOLOGICAL INFORMATION

ENVIRONMENTAL FATE AND DISTRIBUTION: N/A

13 – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: As recommended by local, state and federal authorities.

14 – TRANSPORTATION INFORMATION

PROPER SHIPPING NAME:.... Not D.O.T. regulated. HAZARD CLASS:..... UN/NA NUMBER: PACKAGING GROUP :.....

15 - REGULATIONS

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29CFR 1910.1200

16 – OTHER INFORMATION